

ROYAL MARK

ROYAL MARK Tyre Catalogue

This version is applied
for INDOCHINA IMEXTRA
CO.,LTD

R600 SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R600	295/80R22.5	18	152/149M	1044	3550	3250	900	298	9.00	16

This product cannot be used for lorries truck and buses

R601S SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R601S	275/80R22.5	18	149/146L	1012	3250	3000	900	276	8.25	16
	12R22.5	18	152/149L	1085	3550	3250	930	300	9.00	17.2

This product cannot be used for lorries truck and buses

R602 (ECO) SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R602	12R22.5	18	152/149K	1085	3550	3250	930	300	9.00	14

This product cannot be used for lorries truck and buses

R603 (ECO) SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R603	12R22.5	18	152/149L	1085	3550	3250	930	300	9.00	14

This product cannot be used for lorries truck and buses

R602S SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R602S	12R22.5	18	152/149L	1085	3550	3250	930	300	9.00	17.2

This product cannot be used for lorries truck and buses

R620 SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R620	12R22.5	18	152/149L	1085	3550	3250	930	300	9.00	16.5

This product cannot be used for lorries truck and buses

R668 SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R668	11R22.5	18	149/146M	1054	3250	3000	900	279	8.25	15.5
	11R24.5	16	149/146L	1100	3250	3000	830	279	8.25	15.0
	295/75R22.5	16	146/143L	1015	3000	2750	830	293	9.00	14.5
	295/75R22.5	18	148/145L	1015	3150	2900	900	293	9.00	14.5
	295/80R22.5	18	149/146M	1044	3550	3250	900	298	9.00	18
	315/70R22.5	20	156/150L	1014	4000	3350	930	312	9.00	15.5
	315/80R22.5	20	157/154M	1076	4125	3750	900	312	9.00	17
	315/80R22.5	22	160/157K	1087	4500	4125	970	312	9.00	17
	385/65R22.5	20	160K	1072	4500	4125	900	389	11.75	16
	215/75R17.5	16	127/124L	767	1750	1600	830	211	6.00	14
	225/80R17.5	14	129/127L	805	1850	1750	760	226	6.75	15
	235/75R17.5	16	132/129L	797	2000	1850	830	233	6.75	15
	245/70R17.5	18	134/132L	789	2120	2000	900	248	7.50	15
	245/70R19.5	16	135/133L	839	2180	2060	830	248	7.50	16
	265/70R19.5	16	139/136L	867	2430	2240	830	262	7.50	16

This product cannot be used for lorries truck and buses

R650 SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R650	385/65R22.5	20	160K	1072	4500	4125	900	389	11.75	16.5
	385/65R22.5	22	162K	1072	4500	4125	900	389	11.75	16.5
	385/65R22.5	24	164E	1072	6000	5500	900	389	11.75	16.5

This product cannot be used for lorries truck and buses

R636 SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R636	295/80R22.5	18	152/149L	1044	3550	3250	900	225	9.00	15
				1050	3550	3250	930	298	9.00	15

This product cannot be used for lorries truck and buses

R696 SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R696	12R22.5	20	152/149L	1085	3550	3250	930	300	9.00	18
	275/80R22.5	18	149/146L	1012	3250	3000	900	276	8.25	16.5
	295/80R22.5	18	152/149L	1044	3550	3250	900	298	9.00	16.5

This product cannot be used for lorries truck and buses

R700 SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R700	295/80R22.5	18	152/149M	1044	3550	3250	900	298	9.00	19.5

This product cannot be used for lorries truck and buses

R702 SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R702	11R22.5	16	146/143M	1054	3000	2725	830	279	8.25	20
	11R22.5	18	149/146M	1054	3250	3000	930	279	8.25	20
	315/80R22.5	20	157/154M	1082	4125	3750	900	312	9.00	19.5

This product cannot be used for lorries truck and buses

R708 SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R708	12R22.5	18	152/149L	1085	3550	3250	930	300	9.00	21.5

This product cannot be used for lorries truck and buses

R788 SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R788	215/75R17.5	16	127/124L	767	1750	1600	830	211	6.00	17.5
	295/80R22.5	18	152/149M	1044	3550	3250	930	298	9.00	22.5
	315/80R22.5	20	157/154M	1082	4125	3750	900	312	9.00	22.5
	315/80R22.5	22	160/157K	1087	4500	4125	970	312	9.00	23.0

This product cannot be used for lorries truck and buses

R701 SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R701	12R22.5	18	152/149L	1085	3550	3250	930	300	9.00	19

This product cannot be used for lorries truck and buses

R803 SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Recommended Long Haul
Regional

ROYAL MARK

R805

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R805	295/80R22.5	18	152/149K	1050	3550	3250	930	298	9.00	16
	315/80R22.5	20	157/154M	1080	4125	3750	900	312	9.00	15
	9.00R20	16	144/142K	1019	2800	2650	900	259	7.0	17.5
	10.00R20	18	149/146K	1054	3250	3000	930	278	7.5	18.5
	11.00R20	20	153/150K	1085	3650	3350	930	293	8.0	16.5
	12.00R20	20	156/153K	1125	4000	3650	900	315	8.5	17.5
	12.00R24	20	160/157K	1226	4500	4125	900	316	8.5	24
	11R22.5	18	149/146K	1054	3250	3000	900	279	8.25	16
	13R22.5	18	154/151K	1124	3750	3450	830	320	9.75	18.5

This product cannot be used for lorries truck and buses

R899

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R899	10.00R20	18	149/146K	1054	3250	3000	930	278	7.50	17.0
	11.00R20	20	153/150K	1085	3650	3350	930	293	8.00	18.0
	12.00R20	22	158/155K	1125	4250	3875	900	315	8.50	18.0
	12R22.5	20	152/149K	1085	3550	3250	930	300	9.00	18.0
	13R22.5	20	156/153K	1124	4000	3650	930	320	9.75	18.0

This product cannot be used for lorries truck and buses

R831

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Long Haul
Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R831	12R22.5	18	152/149L	1085	3550	3250	930	300	9.00	18.0

This product cannot be used for lorries truck and buses

R611

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R611	12.00R24	20	160/157K	1226	4500	4125	900	315	8.5	15.5

This product cannot be used for lorries truck and buses

R801S

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R801S	12R22.5	18	152/149L	1085	3550	3250	930	300	9.00	17.7

This product cannot be used for lorries truck and buses

R806

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R806	275/80R22.5	18	149/146K	1012	3250	3000	900	276	8.25	16.5
	12R22.5	18	152/149L	1085	3550	3250	930	300	9.00	17.7

This product cannot be used for lorries truck and buses

R816

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R816	12R22.5	18	152/149L	1085	3550	3250	930	300	9.00	16.5

This product cannot be used for lorries truck and buses

R828

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R828	295/80R22.5	18	152/149M	1044	3550	3250	930	298	9.00	19

This product cannot be used for lorries truck and buses

R902

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



On/Off Road

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R902	9.00R20	16	144/142K	1019	2800	2650	900	259	7.0	17.5
	10.00R20	18	149/146K	1054	3250	3000	930	278	7.5	18.5
	11.00R20	20	153/150K	1085	3650	3350	930	293	8.0	17.5
	12.00R20	20	156/153K	1125	4000	3650	900	315	8.5	19.5
	12R22.5	18	152/149K	1085	3550	3250	930	300	9.00	19
	13R22.5	18	154/151K	1124	3750	3450	830	320	9.75	20

This product cannot be used for lorries truck and buses

R810 (R910)

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R910	11.00R20	20	153/150K	1085	3650	3350	930	293	8.0	17.5
R810	12.00R20	22	158/155K	1125	4250	3875	900	315	8.50	21.5
	13R22.5	20	156/153K	1124	4000	3650	930	320	9.75	21.5

This product cannot be used for lorries truck and buses

R912

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R912	315/80R22.5	20	157/154M	1082	4125	3750	900	312	9.00	20

This product cannot be used for lorries truck and buses

R900

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



Regional

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R900	295/80R22.5	18	152/149K	1044	3550	3250	900	298	9.00	18.5

This product cannot be used for lorries truck and buses

R705

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



On/Off Road

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R705	11R22.5	16	146/143M	1054	3000	2725	830	279	8.25	20
	11R22.5	18	149/146M	1054	3250	3000	930	279	8.25	20
	11R24.5	16	149/146L	1110	3250	3000	830	279	8.25	21
	11R24.5	18	152/149L	1110	3550	3250	900	279	8.25	21
	295/75R22.5	16	146/143L	1026	3000	2750	830	293	9.00	20
	295/75R22.5	18	148/145L	1026	3150	2900	900	293	9.00	20

This product cannot be used for lorries truck and buses

R988

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



On/Off Road

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R988	225/80R17.5	14	129/127K	805	1850	1750	760	192	6.75	17.5
	235/75R17.5	16	132/129K	797	2000	1850	830	233	6.75	17.5
	12.00R24	20	160/157K	1226	4500	4125	900	316	8.5	24

This product cannot be used for lorries truck and buses

R901

SUITABLE FOR ONLY TRAILER OR SEMI-TRAILER



On/Off Road

Pattern	Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity(kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
					Single	Dual				
R901	12R22.5	18	152/149K	1085	3550	3250	930	300	9.00	21.5