

ROYAL MARK

This version is applied
for MYER VIET NAM
IMPORT EXPORT
TRADING COMPANY
LIMITED; only



ROYAL MARK

R600

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R600	285R6002.5	18	132/148H	1004	3500	3200	900	298	9.00	14

*This product cannot be used for fories truck and buses.

R601S

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R601S	275R601S	18	140/148L	1012	3200	3000	900	276	8.25	14
R601S	12R22.5	18	132/148L	1005	3200	3200	900	300	9.00	17.2

*This product cannot be used for fories truck and buses.

R602 (ECO)

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R602	12R22.5	18	132/148L	1005	3200	3200	900	300	9.00	14

*This product cannot be used for fories truck and buses.

R603 (ECO)

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R603	12R22.5	18	132/148L	1005	3200	3200	900	300	9.00	14

*This product cannot be used for fories truck and buses.

R602S

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R602S	12R22.5	18	132/148L	1005	3200	3200	900	300	9.00	17.2

*This product cannot be used for fories truck and buses.

R620

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R620	12R22.5	18	132/148L	1005	3200	3200	900	300	9.00	20.5

*This product cannot be used for fories truck and buses.



R668

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R668	12R22.5	18	140/148H	1004	3200	3000	900	278	8.25	15.5
R668	12R22.5	18	140/148L	1000	3200	3000	900	278	8.25	15.5
R668	240/70R22.5	18	140/148L	1011	3100	2800	900	281	9.00	16.5
R668	240/60R22.5	18	140/148H	1004	3000	2800	900	280	9.00	18
R668	12R22.5	20	150/150L	1014	4000	3300	900	312	9.00	15.5
R668	12R22.5	20	157/158H	1072	4100	3300	900	312	9.00	17
R668	12R22.5	22	160/162H	1067	4500	4100	910	312	9.00	17
R668	12R22.5	20	160H	1072	4000	4100	900	308	11.15	18
R668	215/70R17.5	16	127/124L	787	1700	1600	650	211	6.50	14
R668	215/60R17.5	16	128/127L	800	1600	1500	760	204	6.75	15
R668	240/70R17.5	16	132/129L	797	2000	1800	650	231	6.75	15
R668	240/70R17.5	16	130/132L	789	2100	2000	900	244	7.00	15
R668	240/70R19.5	16	130/135L	839	2100	2000	650	244	7.00	16
R668	240/70R19.5	16	130/136L	867	2400	2300	900	262	7.00	16
R668	0.90R207	12	110/114L	790	1000	910	470	185	5.50F	11.5
R668	1.00R207	14	120/124L	775	1100	1000	770	190	6.00F	13
R668	1.20R207	16	120/121L	895	1400	1400	670	215	6.00F	13.5
R668	0.90R207	14	110/120L	693	2000	1800	670	120	8.00F	15

*This product cannot be used for fories truck and buses.

R650

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R650	380/60R22.5	20	160H	1072	4500	4000	940	309	11.75	16.5
R650	380/60R22.5	22	162H	1072	6700	6000	900	309	11.75	16.5
R650	380/60R22.5	24	168H	1072	8000	7000	900	309	11.75	16.5

*This product cannot be used for fories truck and buses.

R636

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R636	240/60R22.5	18	132/148L	1004	3200	3200	900	220	9.00	13

*This product cannot be used for fories truck and buses.

R696

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R696	12R22.5	18	132/148L	1005	3200	3200	900	300	9.00	18
R696	270/60R22.5	18	140/148L	1012	3200	3000	900	278	8.25	15.5
R696	240/60R22.5	18	132/148L	1004	3200	3200	900	298	9.00	16.5

*This product cannot be used for fories truck and buses.

R700

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R700	240/60R22.5	18	132/148H	1004	3200	3200	900	280	9.00	16.5

*This product cannot be used for fories truck and buses.



R702

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R702	12R22.5	18	140/148H	1004	3000	2750	830	278	8.25	20
R702	12R22.5	18	140/148H	1004	3200	3000	830	278	8.25	20
R702	315/70R22.5	20	157/158H	1082	4100	3750	900	312	9.00	25.5

*This product cannot be used for fories truck and buses.

R708

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R708	12R22.5	18	132/148L	1005	3200	3200	900	300	9.00	21.5

*This product cannot be used for fories truck and buses.

R788

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R788	230/75R17.5	16	127/124L	787	1700	1600	630	211	6.50	17.5
R788	240/60R22.5	18	140/148H	1004	3200	3000	830	278	8.25	21.5
R788	315/60R22.5	20	150/150H	1067	4000	4100	910	312	9.00	23.5

*This product cannot be used for fories truck and buses.

R701

Suitable for only semi-trailer for paved/mixed road of mid-short distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R701	12R22.5	18	132/148L	1005	3200	3200	900	300	9.00	23

*This product cannot be used for fories truck and buses.

R803

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R803	12R22.5	18	132/148L	1005	3200	3200	900	300	9.00	21.5

*This product cannot be used for fories truck and buses.



R707

Suitable for only semi-trailer for paved/mixed road of mid-short distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R707	240/60R22.5	18	132/148H	1005	3200	3200	900	300	9.00	24.5
R707	315/70R22.5	20	150/150H	1067	4000	3700	900	298	9.00	21
R707	315/70R22.5	20	150/150H	1067	4000	3700	900	278	9.00	21

*This product cannot be used for fories truck and buses.

R706

Suitable for only semi-trailer for paved/mixed road of mid-short distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R706	12R22.5	18	132/148H	1005	3200	3200	900	300	9.00	23.5

*This product cannot be used for fories truck and buses.

R812

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R812	12R22.5	18	132/148H	1005	3200	3200	900	300	9.00	29.5

*This product cannot be used for fories truck and buses.

R101

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity/kg (Single)	Load Capacity/kg (Dual)	Inflation Pressure (PSI)	Section Width (mm)	Standart Rim (inch)	Wheel Width (inch)
R101	315/60R22.5	20	157/158H	1080	4100	3750	900	312	9.00	25.5

*This product cannot be used for fories truck and buses.

R802

Suitable for only semi-trailer for paved/mixed road of long-haul distance

Pattern	Size	PR	U.S. SAE	Overall Diameter (mm)	Load Capacity (kg) Single	Load Capacity (kg) Dual	Inflation Pressure (PSI)	Section Width (mm)	Standard Rim (inch)	Wheel Width (inch)
R802	6.00R16LT	12	110/110L	719	1000	910	670	185	5.50F	11
	7.00R16LT	14	118/114L	775	1120	1180	770	200	5.50F	11.5
	7.00R16LT	16	125/121L	865	1400	1490	870	215	6.00G	12
	8.25R16LT	18	131/118L	865	2000	1800	870	215	6.50H	12.5
	312.00R22.5	20	157/154H	1060	4115	3750	900	315	8.25	15
	12.00R20	20	150/153H	1125	4000	3650	900	315	8.5	15

