

ONLY APPLIED FOR VIETNAM MARKET

This version is applied for
INDOCHINA IMEXTRA CO., LTD



2025-2026

SEYOUN SYT620

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



Long Haul
Regional

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
12R22.5	18	152/149L	1085	3550	3250	930	300	9.00	16.5

This product cannot be used for lorries truck and buses



SEYOUN HONSWAY NJK CABALLO FORZA OKATE

SYT668 HSY668 NJK668 CBL668 FZT668 OK668

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



Long Haul
Regional

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
11R22.5	18	149/146M	1054	3250	3000	900	279	8.25	15.5
11R24.5	16	149/146L	1100	3250	3000	830	279	8.25	15.0
295/75R22.5	16	146/143L	1015	3000	2750	830	293	9.00	14.5
295/75R22.5	18	149/145L	1015	3150	2900	900	293	9.00	14.5
295/80R22.5	18	149/146M	1044	3550	3250	900	298	9.00	18
315/70R22.5	20	150/150L	1014	4000	3350	930	312	9.00	15.5
315/80R22.5	20	157/154M	1076	4125	3750	900	312	9.00	17
315/80R22.5	22	160/157K	1087	4500	4125	970	312	9.00	17
385/65R22.5	20	160K	1072	4500	4125	900	389	11.75	16
215/79R17.5	16	127/124L	767	1750	1600	830	211	6.00	14
225/80R17.5	14	129/127L	805	1850	1750	760	226	6.75	15
235/79R17.5	16	132/129L	797	2000	1850	830	233	6.75	15
245/70R17.5	18	134/132L	789	2120	2000	900	246	7.50	15
245/70R19.5	16	135/133L	839	2130	2060	830	246	7.50	16
265/70R19.5	16	139/136L	867	2430	2240	830	262	7.50	16

This product cannot be used for lorries truck and buses



SEYOUN HONSWAY NJK CABALLO FORZA OKATE

SYT696 HSY696 NJK696 CBL696 FZT696 OK696

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



Long Haul
Regional

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
12R22.5	18	152/149L	1085	3550	3250	930	300	9.00	18
275/80R22.5	18	149/146L	1012	3250	3000	900	276	8.25	16.5
295/80R22.5	18	152/149L	1044	3550	3250	900	298	9.00	16.5
11.00R20	18	152/149L	1085	3850	3250	930	298	8.0	16.5
11.00R20	20	150/150L	1085	3950	3350	970	293	8.0	18

This product cannot be used for lorries truck and buses



SEYOUN HONSWAY NJK CABALLO FORZA OKATE

SYT702 HSY702 NJK702 CBL702 FZT702 OK702

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



Long Haul
Regional

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
11R22.5	16	146/143M	1054	3000	2725	830	279	8.25	20
11R22.5	18	149/146M	1054	3250	3000	930	279	8.25	20
315/80R22.5	20	157/154M	1082	4125	3750	900	312	9.00	15.5

This product cannot be used for lorries truck and buses



SEYOUN HONSWAY NJK CABALLO FORZA OKATE

SYT819 HSY819 NJK819 CBL819 FZT819 OK819

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



Long Haul
Regional

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
9.00R20	16	144/142K	1019	2800	2650	900	259	7.0	15.5
10.00R20	18	149/146K	1054	3250	3000	930	278	7.5	16
11.00R20	18	152/149K	1085	3550	3250	930	293	8.00	16.5
11R22.5	16	146/143M	1054	3000	2750	830	279	8.25	15
11R22.5	18	149/146M	1054	3250	3000	930	279	8.25	15
12R22.5	18	152/149K	1085	3550	3250	930	300	9.00	18
12.00R20	20	156/153K	1125	4000	3650	900	315	8.5	17
315/80R22.5	20	157/154M	1076	4125	3750	900	312	9.00	14.5
315/80R22.5	22	160/157K	1076	4500	4125	900	312	9.00	14.5

This product cannot be used for lorries truck and buses



SEYOUN HONSWAY NJK CABALLO FORZA OKATE

SYT805 HSY805 NJK805 CBL805 FZT805 OK805

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



Regional

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
295/80R22.5	18	152/149K	1050	3550	3250	930	298	9.00	16
315/80R22.5	20	157/154M	1080	4125	3750	900	312	9.00	15
9.00R20	16	144/142K	1019	2800	2650	900	259	7.0	17.5
10.00R20	18	149/146K	1054	3250	3000	930	278	7.5	18.5
11.00R20	20	153/150K	1085	3650	3350	930	293	8.0	16.5
12.00R20	20	156/153K	1125	4000	3650	900	315	8.5	17.5
12.00R24	20	160/157K	1226	4500	4125	900	316	8.5	24
11R22.5	18	149/146K	1054	3250	3000	900	279	8.25	16
13R22.5	18	154/151K	1124	3750	3450	830	320	9.75	18.5

This product cannot be used for lorries truck and buses



SEYOUN HONSWAY NJK CABALLO FORZA OKATE

SYT899 HSY899 NJK899 CBL899 FZT899 OK899

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



Regional

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
10.00R20	18	149/146K	1054	3250	3000	930	278	7.50	17.0
11.00R20	20	153/150K	1085	3650	3350	930	293	8.00	18.0
12.00R20	22	158/155K	1125	4250	3875	900	315	8.50	18.0
12R22.5	18	152/149K	1085	3550	3250	930	300	9.00	18.0
13R22.5	20	156/153K	1124	4000	3650	930	320	9.75	18.0

This product cannot be used for lorries truck and buses



SEYOUN HONSWAY NJK CABALLO FORZA OKATE

SYT901 HSY901 NJK901 CBL901 FZT901 OK901

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



On/Off Road

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
12R22.5	18	152/149K	1085	3550	3250	930	300	9.00	21.5

This product cannot be used for lorries truck and buses



SEYOUN HONSWAY NJK CABALLO FORZA OKATE

SYT910 HSY910 NJK910 CBL910 FZT910 OK990

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



Long Haul
Regional

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
11R22.5	16	146/143M	1054	3000	2725	830	279	8.25	20
11R22.5	18	149/146M	1054	3250	3000	930	279	8.25	20
315/80R22.5	20	157/154M	1082	4125	3750	900	312	9.00	19.5

This product cannot be used for lorries truck and buses



SEYOUN HONSWAY NJK CABALLO FORZA OKATE

SYT902 HSY902 NJK902 CBL902 FZT902 OK992

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



On/Off Road

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
9.00R20	16	144/142K	1019	2800	2650	900	259	7.0	17.5
10.00R20	18	149/146K	1054	3250	3000	930	278	7.5	18.5
11.00R20	20	153/150K	1085	3650	3350	930	293	8.0	17.5
12.00R20	20	156/153K	1125	4000	3650	900	315	8.5	19.5
12R22.5	18	152/149K	1085	3550	3250	930	300	9.00	19
13R22.5	18	154/151K	1124	3750	3450	830	320	9.75	20

This product cannot be used for lorries truck and buses



SEYOUN HONSWAY NJK CABALLO FORZA OKATE

SYT996 HSY996 NJK996 CBL996 FZT996 OK996

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



Long Haul
Regional

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
11R22.5	16	146/143M	1054	3000	2725	830	279	8.25	20
11R22.5	18	149/146M	1054	3250	3000	930	279	8.25	20
315/80R22.5	20	157/154M	1082	4125	3750	900	312	9.00	19.5

This product cannot be used for lorries truck and buses



SEYOUN HONSWAY NJK CABALLO FORZA OKATE

SYT903 HSY903 NJK903 CBL903 FZT903 OK993

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



Off Road

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
11.00R20	18	152/149F	1096	3550	3250	930	293	8.0	24.0
12.00R20	20	156/153F	1136	4000	3650	900	315	8.5	24.0
12.00R20	22	156/153B	1136	4000	3650	900	315	8.5	24.0

This product cannot be used for lorries truck and buses



SEYOUN HONSWAY NJK CABALLO FORZA OKATE

SYT908 HSY908 NJK908 CBL908 FZT908 OK999

Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



Long Haul
Regional

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
11R22.5	16	146/143M	1054	3000	2725	830	279	8.25	20
11R22.5	18	149/146M	1054	3250	3000	930	279	8.25	20
315/80R22.5	20	157/154M	1082	4125	3750	900	312	9.00	19.5

This product cannot be used for lorries truck and buses



Suitable for only trailer or semi trailer for paved /mixed road of mid-short distance



Off Road

Recommended Suitable

Size	PR	LI & SS	Overall Diameter (mm)	Load Capacity (kg)		Inflation Pressure (kpa)	Section Width (mm)	Standard Rim (inch)	Tread Depth (mm)
				Single	Dual				
11.00R20	18	152/149F	1096	3550	3250	930	293	8.0	25.5
12.00R20	20	156/153B	1136	4000	3650	900	315	8.5	27.0
12.00R20	24	158/155B	1136	4250	3875	960	315	8.5	27.0

This product cannot be used for lorries truck and buses

